









PCLX 320 'STREETWORKS' PLATE COMPACTOR





FEATURES & BENEFITS

- Low Hand-Arm Vibration design for longer safe usage times.
- 'Dual Force' base plate provides added compaction to meet UK HAUC requirements.
- The baseplate is made from Strenx™ performance steel with a Hardox® wear plate for added strength and durability.
- Tubular frame designed to protect vulnerable components.
- Lightweight yet durable for easy transport
- Removable 12 litre water tank features a quick-release design.
- Fitted with manual handling points.
- High power 13kN vibration force.
- Engineered to be robust and durable for rental and heavy contractor usage.
- Lightweight yet durable for easy transport.
- Fitted with manual handling points.
- High power 13kN vibration force.
- Improved productivity with fast travel speeds.

TECHNICAL SPECIFICATIONS

Model	PCLX 320 'STREETWORKS'	
Part No.	LX3251	
Width	(mm)	320
Operating Height	(mm)	928
Operating Length	(mm)	875
Storage Height	(mm)	590.5
Storage Length	(mm)	775
Plate Contact Area (W x L)	(mm)	320 x 390
Plate Length	(mm)	417
Engine Power	(Hp / kW)	3/2.2
Engine RPM		3850
Weight	(kg)	65
Static Pressure	(kg/m^2)	1611
Centrifugal Force	(kN)	13
Travel Speed	(m/min)	18
Vibration level	(m/sec^2)	2.14



8HRS+ SAFE MACHINE



13KN VIBRATION UNIT



'DUAL FORCE' BASEPLATE FROM STRENX™ PERFORMANCE STEEL WITH HARDOX® WEAR PLATE



PCLX3205 Water Spray Kit



ALTRAD BELLE
Sheen, Nr. Buxton, Derbyshire, SK17 OEU, GB
Tel. +44 (0)1298 84606 - Fax +44 (0)1298 84722 - Email: sales@altrad-belle.com
www.Altrad-Belle.com
www.ALTRAD-Belle247.com

OPP/57S/DIO

Options

