



# MBX 12/180

## MINI BOWSER PRESSURE WASHER

The 125-litre MBX 12/180 Mini Bowser Pressure Washer is designed to satisfy the demands of individuals who need maximum mobility without compromising performance.

It guarantees a sufficient water supply or cleaning tasks whilst on the go and has the power to remove even the toughest dirt and grime from a range of surfaces.



#### **FEATURES & BENEFITS**

- Robust, compact full engine & pump protection frame complete with hose storage facility as standard.
- 125 litre durable polyethylene water tank with filler strainer as standard.
- Professional Honda petrol engine with recoil start.
- Detergent / chemical feed-line complete with strainer filter.
- Single point lift to minimize manual handling risk.
- Accessible service points.
- Inlet-line strainer for added pump protection.
- Low engine oil cut-off.
- High quality, heavy-duty triple piston pump.
- Professional two-wire, 10m braided hose, complete with quick-screw adapters and swivel couplings.
- Thermal pump protection.
- Lance holder integrated into protection frame.
- Lance comes complete with safety trigger lock.
- 4-ply deep-tread tyre as standard.
- Specifically designed for hire and rental markets.
- Customer colour options available.
- Optional 10m Hose Reel available.
- Puncture-proof foam filled tyre option available.

### **TECHNICAL SPECIFICATIONS**

| Model               |             | MBX 12/180  | MBX 12/180   |
|---------------------|-------------|-------------|--------------|
|                     |             | Standard    | cw Hose Reel |
| Part No.            |             | MBX121801S  | MBX121801RS  |
| Length              | (mm)        | 1378        | 1378         |
| Width               | (mm)        | 760         | 760          |
| Height              | (mm)        | 885         | 885          |
| Unladen Weight      | (kg)        | *91         | **100        |
| Max. Laden Weight   | (kg)        | #223.5      | ##227        |
| Water Flow          | (Ipm)       | 12          | 12           |
| Max. Water Pressure | (bar-psi)   | 180-2600    | 180-2600     |
| Engine              |             | Honda GX200 | Honda GX200  |
| Engine Power        | (Hp / kW)   | 5.8 / 4.3   | 5.8 / 4.3    |
| Engine RPM          |             | 3400        | 3400         |
| Water Tank Capacity | (Ltrs)      | 125         | 125          |
| Fuel Tank Capacity  | (Ltrs)      | 3.1         | 3.1          |
| Hose Length         | (M)         | 10          | 10           |
| Tyre Size           | (mm)        | 400-8       | 400-8        |
| Tyre Pressure       | (psi - bar) | 30 - 2.1    | 30 - 2.1     |
| Gearbox Driven Pump |             | Yes         | Yes          |
|                     |             |             |              |

<sup>\*</sup> without lance and hose. \*\* without lance.

#### **Options**

OPPW/08/DIO 10m Hose Reel Kit 80108 Puncture Proof Tyre



HOSE STORAGE INTEGRATED INTO PROTECTION FRAME



TANK FILLER STRAINER AS STANDARD



**HOSE REEL OPTION** 



PUNCTURE PROOF, FOAM-FILLED
TYRE OPTION



<sup>#</sup> with lance and hose. ## with lance